

Flexible Duct Series



Aluminum Foil Flexible Duct

Material: Aluminum foil enhanced with spiral steel wire
 Standard length: 10M
 Max. air velocity: 30M/S
 Temperature range: -20°C to +120°C
 Max. operation pressure: 250mmWG
Feature: Extraordinary flexible to fit on round or oval connections.

Model	Size
S-03	3"
S-04	4"
S-06	6"
S-08	8"
S-10	10"
S-12	12"
S-14	14"



Insulated Aluminum Foil Flexible Duct

Material: Aluminum foil 25MM thick 16 Kg/M³-24Kg/M³ fiberwool
 Standard length: 10M
 Max. air velocity: 30M/S
 Temperature range: -20°C to +120°C
 Max. operation pressure: 250mmWG

Enhanced Al. Foil	Fiberglass	Size
SA-4	SB-4	4"
SA-6	SB-6	6"
SA-8	SB-8	8"

Feature: Aluminum foil enhanced with spiral steel wire, covered with 25mm thick 16 kg/m³-24 kg/m³ fiberwool then coated with enhanced aluminum foil (SA-series) or fiberglass cloth (SB-series). Extraordinary flexible to fit on round or oval connections.



Insulated Aluminum Foil Flexible Duct

Material: Aluminum foil 25MM thick 16Kg/M³-24Kg/M³ fiberwool
 Standard length: 10M
 Max. air velocity: 30M/S
 Temperature range: -20°C to +120°C
 Max. operation pressure: 250mmWG

Enhanced Al. Foil	Fiberglass	Size
SA-10	SB-10	10"
SA-12	SB-12	12"
SA-14	SB-14	14"

Feature: Aluminum foil enhanced with spiral steel wire, covered with 25mm thick 16 kg/m³-24 kg/m³ fiberwool then coated with enhanced aluminum foil (SA-series) or fiberglass cloth (SB-series). Extraordinary flexible to fit on round or oval connections.



Aluminum Flexible Duct

Material: Aluminum
 Thickness: 0.8-1.2mm
 Length: Per customers' request
 Diameter: 3"-16"
Feature: Extraordinary flexibility and extensibility. May bend or extend to your need.

Model	Size
SFC-03	3"
SFC-04	4"
SFC-06	6"
SFC-08	8"
SFC-10	10"
SFC-12	12"
SFC-14	14"
SFC-16	16"


Flexible Duct / Spiral Tubing/ Aluminum Alloy Diffuser



Fiberglass-Aluminum Foil Composite Flexible Duct

Material: Fiberglass cloth and aluminum foil.
 Standard length: 10M
 Max. air velocity: 30M/S
 Temperature range: -20°C to +120°C
 Max. operation pressure: 250mmWG
Feature: Double layers by fiberglass cloth and enhanced aluminum foil. Enhanced with built in spiral steel wire. Won't break when bent or extend. Easy to install. Extraordinary ideal for ventilation.

Model	Size
SFE-02	2"
SFE-03	3"
SFE-04	4"
SFE-06	6"
SFE-08	8"
SFE-10	10"
SFE-12	12"
SFE-14	14"



Spiral Tubing

Material: Galvanized steel sheet / Stainless steel
 Length: Per customers' design
 Diameter: 3"-6", 8", 10", 12", 14", 16", 18", 20", 22", 24", -26".
 Thickness: #26(0.5"/.)-#20(1.0"/.).
Feature: Spiral overlapping structure, enhance the strength and toughness. Excellent air seal, minimize air friction.


Model	Size
SFG-03-06	3"-6"
SFG-08	8"
SFG-10	10"
SFG-12	12"
SFG-14	14"
SFG-16	16"
SFG-18	18"
SFG-20	20"
SFG-22	22"
SFG-24-60	24"-60"



Square Type Air Diffuser

Material: Aluminum alloy
 Structure: Split design for inner louvers and outer frame.
Feature: 1-way blow to 4 way blow types are available.
 Option: May add opposite blades damper, adapter.
 Size : Per customers' design
 (Please confirm base size or neck size when order.)

Aluminum Alloy Air Diffuser Series



Circular Type Air Diffuser

Material: Aluminum alloy
 Structure: Split design for inner rings.
Feature: Special design for best air spread.
 Size: Per customers' design
 (Please confirm base size or neck size when order.)

